




Terra-Mulch® Terra-Wood™ with UltraGro™ Wood Fiber

Delivers up to 30% more coverage than competitive brands

- Terra-Wood™ contains 100% of the highest-grade Thermally Refined® wood fiber
- Thermally Refined wood fiber delivers up to 50% more water-holding capacity than atmospherically refined wood mulches
- Now combined with UltraGro™—a proprietary biostimulant
- UltraGro increases root mass to improve nutrient and water uptake, giving plants greater stress tolerance
- Terra-Wood forms an interlocking ground cover, which readily absorbs water and allows infiltration to the underlying soil
- Non-toxic and environmentally safe
- Meets or exceeds all requirements for wood fiber mulch
- Maximum slope length of 28 feet
- Use approved hydroseeding equipment for optimum pumping and application performance
- Terra-Wood with UltraGro functional longevity is ≤ 3 months



Product Composition:

Thermally Refined® Wood Fibers – 87% \pm 3%

UltraGro™ – 1% \pm 0.5%

Moisture Content – 12% \pm 3%

(40) 50-lb bales per pallet

Slope Gradient/Condition

<u>Slope Gradient/Condition</u>	<u>Rate</u>
$\leq 4H:1V$	2000 lb/acre
$> 4H:1V$ and $\leq 3H:1V$	2500 lb/acre
$> 3H:1V$ and $\leq 2H:1V$	3000 lb/acre



PROFILE Products LLC · 750 Lake Cook Road · Suite 440 · Buffalo Grove, IL 60089

Technical Assistance: 800-508-8681

www.profileproducts.com