

PAM-12[®] Plus - Landscape



The only granular mulch that keeps soil, seed and fertilizer on slopes – even after a storm



PAM-12[®] Plus

Holds Seed Keeps soil, seed and fertilizer on sloped surfaces right where you left it, even after a storm

Saves Money Has double the coverage of other granular mulches

Saves Time Simply apply with a spreader and you are finished. No mess to clean up, or stakes to install

Apply Wet or Dry Can be applied with hydro-seeding equipment or broadcast spreaders

Easy to Use Easy to store and handle. Can be applied with a broadcast spreader



AST[®] –

Advanced Soil Technology™

AST[®] is a biodegradable polymer blend that acts like a net over your jobsite to hold soil, seed and fertilizer in place.

PAM-12[®] Plus is proven by ASTM D6459 Standards.

PAM-12[®] Plus

ENCAP's PAM-12[®] Plus is a granular mulch that can be applied with most broadcast spreaders. The granules are made from recycled paper and contain ENCAP's proprietary blend of soil stabilizing polymers. The polymers are designed to improve soil conditions and keep seed, soil and fertilizer on sloped surfaces right where you put them, even after it rains. The polymers also help to condition the soil by creating micro

channels that help to get water and nutrients into the root zone. This improves germination and overall seed establishment.

All of this in a product that is clean and easy to use. ENCAP's PAM-12[®] Plus is fast and easy to apply with no cleanup saving you time, money and labor. PAM-12[®] Plus is the earth – friendly choice of landscape professionals.

Application Rates

Slope	Lbs/1000 ft ²
No Slope up to 4:1	25
4:1 – 3:1 Slope	25 - 50
3:1 – 2:1 Slope	50 - 75

Dry Application Guidelines

Apply uniformly using the above rates



25 lbs / 1000 ft²



50 lbs / 1000 ft²

Please Note:

- Application rates and methods may vary based on site conditions such as slope, soil type, physical state and chemical properties of the soil and time of year
- Application rates may vary based on desired visual appearance
- Slope interruption devices are recommended on slopes exceeding 40ft in length
- PAM-12[®] Plus granules are activated by natural or applied moisture
- It is recommended that seeding be completed prior to applying PAM-12[®] Plus. Seed needs to be in direct contact with the soil on a well prepared seed bed
- For more information visit our website at www.encapro.com

Guaranteed Analysis

- 75.4% Engineered Paper Fibers
- 1.5% Polyacrylamide copolymer (solid)
- 2.1% Polyacrylamide copolymer (emulsion)
- 1.0% Biopolymer
- 20% Gypsum (prilled calcium sulfate dihydrate)

Hydraulic Application Guidelines

PAM-12[®] Plus granules are designed to visually ensure even distribution of polymer throughout the tank to dramatically reduce loading and mixing time. Mix per the following:

Mixing Instructions: Mix at a ratio of 1 gallon of water per pound of PAM-12[®] Plus.

Stand Alone: Apply uniformly using the above rates.

With cover mulch: Replace 1 lb of tackifier and 50 lbs of cover mulch with 50lbs PAM-12[®] Plus. Adjust the ratio of PAM 12[®] Plus to cover mulch according to desired visual appearance and necessary degree of stabilization.



ENCAP LLC
 3921 Algoma Road
 Green Bay, WI 54311
877-405-5050
 920-406-9740 (fax)
www.encapro.com

